


## SAFETY DATA SHEET

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION			
Product Description	Lithium-Ion Rechargeable Cells and Batteries		
Product Identification	For <b>Identification By Chemistry</b> see Section 3. For <b>NSN listing</b> see section 16.		
Manufacturer Name/Address	Ultralife Corporation 2000 Technology Parkway Newark, NY 14513	24 Hour Emergency Contact	ChemTrec 800-424-9300 (US) 703-527-3887 (International)
Technical Contact	800-332-5000	Issue Date	23 MAY 02
Prepared By	Dave Gould	Revision Date:	10 MAR 22

Section 2 - HAZARDS IDENTIFICATION
<p>NOTE: This Ultralife battery product meets the definition of an article. Under the Globally Harmonized System of Classification and Labeling of Chemicals (GHS), "Articles" as defined in the Hazard Communication Standard (29 CFR 1910.1200) of the Occupational Safety and Health Administration of the United States of America, or by similar definition, are outside the scope of the system. [Rev. 2 (2007) Part 1.3.2.1.1]</p> <p><b>The materials contained in this product may only represent the hazards identified below if the integrity of the cell or battery is compromised; physically or electrically abused.</b></p> <p><b><u>GHS Classification</u></b></p> <p>Skin irritation (Category 2) Skin sensation (Category 1) Eye irritation (Category 2) Single target organ toxicity, single exposure (Category 3) Carcinogen (Category 1B)</p> <p><b><u>GHS Label elements, including precautionary statements</u></b></p> <p>Pictogram</p>  <p>Signal word – DANGER</p> <p><b><u>Hazard statements</u></b></p> <p>H315 Causes skin irritation H317 May cause an allergic skin reaction H319 Causes serious eye irritation H335 May cause respiratory irritation H350 May cause cancer</p>

ANY PHOTOCOPY MUST BE OF THIS ENTIRE DOCUMENT

**SAFETY DATA SHEET****Precautionary statements**

P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P312 Call a POISON CENTER or doctor/physician if you feel unwell.  
P302 + P352 IF ON SKIN: gently wash with plenty of soap and water.  
P301 + P330 + P331 IF SWALLOWED: rinse mouth, DO NOT induce vomiting.  
P304 + P340 IF INHALED: Move person to fresh air and keep comfortable for breathing.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes.  
P362 + P352 Take off contaminated clothing and wash before re-use.  
P501 Dispose of contents/container in accordance with local/national regulations.

**WHMIS Classification**

D2A Very toxic material causing other toxic effects

Carcinogen

D2B Toxic material causing other toxic effects

Moderate skin irritant

Skin sensitizer

Moderate respiratory irritant

Moderate eye irritant

**OSHA Classification**

Hazardous

**HMIS Classification**

Health Hazard: 2

Chronic Hazards: 0

Flammability: 2

Physical Hazards: 0

**Additional Notes:**

- Do not open or disassemble.
- Do not expose to fire or open flame.
- Do not mix with batteries of varying sizes, chemistries or types.
- Do not puncture, deform, incinerate or heat above 85°C (185°F).

**ANY PHOTOCOPY MUST BE OF THIS ENTIRE DOCUMENT**

**SAFETY DATA SHEET**

**SECTION 3 - COMPOSITION – INGREDIENTS INFORMATION**

**Lithium Cobalt Oxide Type:**

12041-2100-01, 12041-2100-02, 12041-2100-03, A3307643, S00072, S00112, S00145, S00225, S00245, S00273, S00301, S00304, S00314, S00335, UBBL02, UBBL03, UBBL06, UBBL08, UBBL09/B, UBBL10, UBBL10/B, UBBL18, UBBL19, UBBL20, UBBL21, UBBL22, UBBL23, UBBL24, UBBL25, UBBL26, UBBL27, UBBL29, UBBL29/B, UBBL31, UBBL35, UBBL64, UBBL65, UBBP01, UBPO01, UBPO02, UBPO10.

**Under normal use conditions, cells and batteries do not emit hazardous or regulated substances.**

Component	CAS Number	EINECS Number	% by Wt.
Lithium Cobalt Oxide	12190-79-3	NA	10-45
Graphite	7440-44-0	NA	5-20
Ethylene Carbonate – Solvent	96-49-1	NA	3-6
Diethyl Carbonate – Solvent	105-58-8	203-311-1	3-6
Lithium Hexafluorophosphate – Salt	21324-40-3	NA	1-5

Depending on product configuration, components used to assemble battery packs (e.g. housings, electronic components and wiring) may contain additional hazardous materials, such as lead solder.

**SECTION 3 (Continued) - COMPOSITION - INGREDIENTS INFORMATION**

**Lithium Nickel Cobalt Aluminum Type:**

1009761, 12041-2200-01, 12041-2200-02, 12041-2200-03, 12041-2400-01, 12041-2400-02, 12041-2400-03, 12041-2420-02, 12500-2500, 299-0600, 817724-6, S00343, SCP0570008, SCP0570117, UBBL02-01, UBBL02-01-CB, UBBL06-01, UBBL06-02, UBBL08-01, UBBL10-01, UBBL10-01-CB, UBBL13, UBBL13-01, UBBL13-01-CB, UBBL34, UBBL36, UBBL38, UBBL39, UBBL62, UBBP06, M975158Axxx, 14002-0214-01, 14002-0214-02, 14035-4010-01, 14035-4010-02, 14035-5050-01, 14035-5050-02.

**Under normal use conditions, cells and batteries do not emit hazardous or regulated substances.**

Component	CAS Number	EINECS Number	% by Wt.
Lithium Cobalt Nickel Aluminum Oxide	193214-24-3	NA	10-45
Graphite	7440-44-0	NA	5-20
Ethylene Carbonate – Solvent	96-49-1	NA	3-6
Diethyl Carbonate – Solvent	105-58-8	203-311-1	3-6
Lithium Hexafluorophosphate – Salt	21324-40-3	NA	1-5

Depending on product configuration, components used to assemble battery packs (e.g. housings, electronic components and wiring) may contain additional hazardous materials, such as lead solder.

**ANY PHOTOCOPY MUST BE OF THIS ENTIRE DOCUMENT**

## SAFETY DATA SHEET

### SECTION 3 (Continued) - COMPOSITION - INGREDIENTS INFORMATION

**Lithium Nickel Manganese Cobalt Type:**

S00216, S00319, S00209, UBBL05, UBBL07.

**Under normal use conditions, cells and batteries do not emit hazardous or regulated substances.**

Component	CAS Number	EINECS Number	% by Wt.
Lithium Nickel Manganese Cobalt Oxide	346417-97-8	NA	10-45
Graphite	7440-44-0	NA	5-20
Ethylene Carbonate – Solvent	96-49-1	NA	3-6
Diethyl Carbonate – Solvent	105-58-8	203-311-1	3-6
Lithium Hexafluorophosphate – Salt	21324-40-3	NA	1-5

Depending on product configuration, components used to assemble battery packs (e.g. housings, electronic components and wiring) may contain additional hazardous materials, such as lead solder.

### SECTION 4 - FIRST AID MEASURES

Inhalation	<ul style="list-style-type: none"> <li>Avoid inhaling any vented gases.</li> <li>Remove to fresh air immediately.</li> <li>If breathing is difficult, seek emergency medical attention.</li> </ul>
Ingestion	<ul style="list-style-type: none"> <li>Consult a physician or local poison control center immediately</li> </ul>
Skin Contact	<ul style="list-style-type: none"> <li>Exposure to materials from a ruptured or otherwise damaged cell or battery may cause skin irritation.</li> <li>Flush immediately with water and wash affected area with soap and water.</li> </ul>
Eye Contact	<ul style="list-style-type: none"> <li>Exposure to materials from a ruptured or otherwise damaged cell or battery may cause eye irritation.</li> <li>Flush immediately with copious amounts of water for at least 15 minutes; consult a physician immediately.</li> </ul>

### SECTION 5 - FIRE FIGHTING MEASURES

Extinguishing Media	<ul style="list-style-type: none"> <li>Copious amounts of cold water or water-based foam may be used to cool burning cells or batteries. Do not use warm or hot water.</li> <li>A carbon dioxide (CO<sub>2</sub>) extinguisher is also effective.</li> <li>For fires involving exposed, raw lithium metal (characterized by deep red flames), use only metal (Class D) fire extinguishers.</li> <li>Do not use Halon type extinguishing material.</li> </ul>
Special Fire Fighting Procedures	<ul style="list-style-type: none"> <li>Use a positive pressure self-contained breathing apparatus (SCBA) if cells or batteries are involved in a fire.</li> <li>Full fire fighting protective clothing is necessary.</li> </ul>

**ANY PHOTOCOPY MUST BE OF THIS ENTIRE DOCUMENT**

## SAFETY DATA SHEET

	<ul style="list-style-type: none"> <li>During water application, caution is advised as burning pieces of flammable particles may be ejected from the fire.</li> </ul>
Unusual Fire and Explosion Hazard	<ul style="list-style-type: none"> <li>Cells or batteries that are damaged, opened or exposed to excessive heat/fire may flame or leak potentially hazardous organic vapors.</li> </ul>

### SECTION 6 - ACCIDENTAL RELEASE MEASURES

- In the event a cell or battery is crushed; releasing its contents, rubber gloves must be used to handle all battery components.
- Avoid inhalation of any vapors that may be emitted.
- Damaged batteries that are not hot or burning should be placed in a sealed plastic bag or container.

### SECTION 7 - HANDLING AND STORAGE

Precautions for Safe Handling	<ul style="list-style-type: none"> <li>Batteries are designed to be recharged. However, improperly charging a cell or battery may cause the product to flame or leak. Use only approved chargers and procedures.</li> <li>Never disassemble a battery or bypass any safety device.</li> <li>More than a momentary short circuit will cause temporary battery voltage loss until the battery is subjected to a charge. Batteries have re-settable fuses that can be reactivated through applying a charge to the battery.</li> <li>Extended short-circuiting creates high temperatures in the cell.</li> <li>High temperatures can cause burns in skin or cause the cell to flame.</li> <li>Avoid reversing battery polarity within the battery assembly. To do so may cause cell to flame or to leak.</li> </ul>
Conditions for Safe Storage and Incompatibility	<ul style="list-style-type: none"> <li>Batteries should be separated from other materials and stored in a non-combustible, well ventilated structure with sufficient clearance between walls and battery stacks. Do not place batteries near heating equipment, nor expose to direct sunlight for long periods.</li> <li>Do not store batteries above 60°C (140°F) or below -20°C (-4°F). Store batteries in a cool (below 25°C (77°F)), dry area that is subject to little temperature change. Elevated temperatures can result in reduced battery service life. Battery exposure to temperatures in excess of 130°C (266°F) will result in the battery venting flammable liquid and gases.</li> <li>Do not store batteries in a manner that allows terminals to short circuit.</li> </ul>

ANY PHOTOCOPY MUST BE OF THIS ENTIRE DOCUMENT

## SAFETY DATA SHEET

### SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls and Work Practices	<ul style="list-style-type: none"> <li>Under conditions of normal use, batteries do not emit hazardous or regulated substances.</li> <li>No engineering controls are required for handling batteries that have not been damaged.</li> </ul>
Personal Protective Equipment	<ul style="list-style-type: none"> <li>Personal protective equipment for damaged batteries should include chemical resistant gloves and safety glasses.</li> <li>In the event of a fire, SCBA should be worn along with thermally protective outer garments.</li> </ul>

### SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Cylindrical cell or pack	UEL/LEL	Not Applicable
Odor	None	Vapor Pressure	Not Applicable
Odor Threshold	Not Applicable	Vapor Density	Not Applicable
pH	Not Applicable	Relative Density	Not Available
Melting Point	Not Available	Solubility	Not Applicable
Boiling Point	Not Available	Partition Coefficient	Not Applicable
Flash Point	Not Applicable	Auto-ignition Temperature	Not Available
Evaporation Rate	Not Applicable	Decomposition Temperature	Not Available
Flammability	Not Applicable	Viscosity	Not Applicable

### SECTION 10 - STABILITY AND REACTIVITY

Stability:	Stable
Hazardous Polymerization:	Will Not Occur
Conditions to Avoid:	Prolonged overcharging and/or overheating. It is not recommended that this product be stored above 60°C (140°F).
Hazardous Decomposition:	Carbon Monoxide (CO), and Hydrogen Fluoride (HF)
Reactivity:	Damaged non-discharged batteries contain elemental Lithium that is water reactive. This reaction gives off heat and hydrogen gas

ANY PHOTOCOPY MUST BE OF THIS ENTIRE DOCUMENT

**SAFETY DATA SHEET****SECTION 11 – TOXICOLOGICAL INFORMATION**

- No toxicological impacts are expected under normal use conditions.
- The electrolytes contained in this cell or battery can irritate eyes with any contact.
- Prolonged contact of electrolytes with lung tissue, skin or mucous membranes may cause irritation.
- Detailed information regarding sensitization, carcinogenicity, mutagenicity or reproductive toxicity related to internal cell or battery components has not been included in this document.

**Carcinogen References**

1. National Toxicology Program (NTP): No
2. IARC Monographs: No
3. OSHA: No

**SECTION 12 – ECOLOGICAL INFORMATION**

- No ecological impacts expected under normal use conditions.
- Information on the ecological impact of internal cell or battery components has not been included in this document.

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Do not dispose in fire. Battery disposal regulations vary on national, state/provincial and local bases.

**Disposal must be conducted in accordance with the applicable regulations.**

**These batteries contain recyclable materials and recycling is encouraged over disposal.**

**SECTION 14 - TRANSPORTATION INFORMATION**

Ultralife's lithium metal primary cells and batteries and lithium-ion cells and batteries are classified and regulated as Class 9 dangerous goods (also known as "hazardous materials" in the United States) by the International Civil Aviation Organization (ICAO), International Air Transport Association (IATA), International Maritime Organization (IMO) and many government agencies such as the U.S. Department of Transportation (DOT). These organizations and agencies publish regulations that contain detailed packaging, marking, labeling, documentation, and training requirements that must be followed when offering (shipping) Ultralife's cells and batteries for transportation. **However, small cells and batteries are not subject to certain provisions of the regulations (e.g. Class 9 labeling and UN specification packaging) if they meet specific requirements.** The regulations are based on the UN Recommendations on the Transport of Dangerous Goods Model Regulations and the UN Manual of Tests and Criteria. **These regulations also apply to shipments of cells and batteries that are packed with or contained in equipment.** Failure to comply with these regulations can result in substantial civil or criminal penalties.

**ANY PHOTOCOPY MUST BE OF THIS ENTIRE DOCUMENT**

**SAFETY DATA SHEET**

The dangerous goods regulations require that each cell and battery design be subject to tests contained in Section 38.3 of the UN Manual of Tests and Criteria prior to being offered for transport.

**Approved, production level cells and batteries manufactured and assembled by Ultralife have been tested to Section 38.3 of the UN Manual of Tests and Criteria and passed T1 through T8.**

Batteries or battery packs constructed by other parties using Ultralife's cells must be subjected to the tests contained in Section 38.3 of the UN Manual of Tests and Criteria.

**Important Note Regarding Prototype Cells and Batteries**

Ultralife Corporation is permitted to ship prototype cells and batteries as Class 9 hazardous materials/dangerous goods in accordance with the requirements contained in a competent authority approval; provided by the US Department of Transportation. Recipients of these shipments are prohibited from reshipping unless they have received a similar approval from the governing Competent Authority.

**SECTION 14 - TRANSPORTATION INFORMATION (continued)**

Air, Sea and Surface Classification	UN 3480, Lithium Ion batteries UN 3481, Lithium Ion batteries, contained in equipment UN 3481, Lithium Ion batteries, packed with equipment
-------------------------------------	---

**IATA Packaging Guidance**

UN3480 Lithium Ion Batteries:  
     PI965 Section IA batteries more than 100Wh or single cell more than 20Wh.  
           Section IB batteries less than 100Wh or single cell less than 20Wh -.  
           Section II batteries less than 100Wh or single cell less than 20Wh -max 2 batteries

UN3481 Lithium Ion Batteries contained in Equipment  
     PI967 Section I batteries more than 100Wh or single cell more than 20Wh.  
           Section II batteries less than 100Wh or single cell less than 20Wh

Lithium Ion Batteries packed with equipment  
     PI966 Section I batteries more than 100Wh or single cell more than 20Wh.  
           Section II batteries less than 100Wh or single cells less than 20Wh

Hazard Class	9	Tunnel Code	E		
Stowage Location	A	Marine Pollutant	No		

**ANY PHOTOCOPY MUST BE OF THIS ENTIRE DOCUMENT**



**SAFETY DATA SHEET**

<b>SECTION 15 - REGULATORY INFORMATION</b>		
US	Hazard Communication Standard (29 CFR 1910.1200)	Article
	CERCLA SECTION 304 Hazardous Substances	NA
	EPCRA SECTION 302 Extremely Hazardous Substance	NA
	EPCRA SECTION 313 Toxic Release Inventory	NA
	EPCRA SECTION 312	NA
	Components Listed on US Toxic Substances Control Act (TSCA) Inventory	Yes
	California Prop 65 Classification	None
EU	Registration, Evaluation, Authorization and Restriction of Chemicals (REACH) 1907/2006	Article
	European RoHS2 Directive 2011/65/EU	Not Applicable
	European WEEE Directive 2012/19/EU Note: Applies to cells and batteries incorporated into electrical and electronic equipment, when that equipment becomes waste.	See Note

<b>SECTION 16 - OTHER INFORMATION</b>
<p>If returning product to any division of Ultralife, consult the relevant regulations regarding handling, packaging, labeling and transportation.</p> <p><u>For UBBL29 and UBBL29/B Products</u></p> <p>External Battery Finish – Reference MSDS for Sherwin Williams MIL-DTL-64159 (approx. 8 grams)                      PCB Coating – Reference MSDS for Humiseal 1B73 Aerosol (approx. 0.6 grams)                      Li-Ion Cells – Reference MSDS for Molicel Cobalt-based Lithium-Ion Cells (approx. 768 grams)</p> <p><u>For UBBL31 Products</u></p> <p>Battery Case Material – Reference MSDS for Sabic Noryl® N190X-701 (approx. 132 grams)                      PCB Coating – Reference MSDS for Humiseal 1B73 Aerosol (approx. 0.6 grams)                      Li-Ion Cells – Reference MSDS for Molicel Cobalt-based Lithium-Ion Cells (approx. 1152 grams)</p> <p><u>NSN # List</u></p> <p>6140-01-553-3527 (for UBBL02, UBBL02-01)                      6140-01-620-0555 (for UBBL03)                      6140-01-542-4380 (for UBBL06)                      6140-01-590-4132 (for UBBL07)                      6140-01-580-6190 (for UBBL08)                      6140-01-620-8528 (for UBBL09/B)                      6140-01-554-2347 (for UBBL10, UBBL10-01)</p>

**ANY PHOTOCOPY MUST BE OF THIS ENTIRE DOCUMENT**

**SAFETY DATA SHEET**

6140-01-611-0192 (for UBBL13, UBBL13-01)  
6140-01-625-9659 (for UBBL13-01)  
6140-01-573-4968 (for UBBL29)  
6140-01-583-0570 (for UBBL29/B)  
6140-01-573-6374 (for UBBL31)  
6140-01-625-7254 (for UBBL35)  
6140-01-592-5521 (for A3307643-1)  
6140-01-592-5521 (for 1009761)  
6140-01-551-8898 (for 12041-2100-01)  
6140-01-548-7566 (for 12041-2100-02)  
6140-01-628-0941 (for 12041-2100-03)  
6140-01-612-9653 (for 12041-2200-01)  
6140-01-548-7566 (for 12041-2200-02)  
6140-01-548-7566 (for 12041-2400-02)  
6140-01-678-7176 (for 12500-2500-02)

**Disclaimer**

The information contained herein is furnished without warranty of any kind. Users should consider this data only as a supplement to other information gathered by them and must make independent determinations of the suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers.

**ANY PHOTOCOPY MUST BE OF THIS ENTIRE DOCUMENT**